
Subject: Freeing handles question.

Posted by [Russ Welti](#) on Wed, 23 Aug 1995 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

Can anyone summarize in plain English:

"Precisely when it is critical to free handles?"

For example, if I point handles to things which are in COMMON blocks, I assume I don't want/need to free the handles when it is time to point them to a new item. BUT if I point these handles to items created local to a routine and exit that routine while still having the handle set and accessible, then I better remember to free it at some point... (?)

One can generate quite complex scenarios w/arrays of structures which have handles to various places, and if the array must be completely rebuilt (suppose the user 'opens' a new "file") then can I just destroy and rebuild my complex array? What guides my decision?

Another way to phrase this is "What are the most common pitfalls to using handles, in a nutshell?"

I confess that I do NOT make the use of them that I could/should, merely because it is somewhat of a mystery to me what my duties are to use them correctly. I only know when I **don't** use them correctly (core dump). I would like to see them explained in terms of malloc and free.

Russ Welti

/-\
(c-g)

University of Washington

\-/

Molecular Biotechnology

/

PO Box 352145

/-\
(a-t)

Seattle, WA 98195

rwelti@u.washington.edu

\-/

(206) 685 4449 voice (206) 685 ???? FAX /

<http://chroma.mbt.washington.edu/graphics/gif/russ.gif>
