Subject: Re: Grouping adjacent detected pixels? Posted by Thomas A McGlynn on Mon, 28 Aug 1995 07:00:00 GMT View Forum Message <> Reply to Message

```
grunes@news.nrl.navy.mil (Mitchell R Grunes) wrote:
> Subject: Grouping adjacent detected pixels?
> I have an image of "detected" points--
> True for pixels meeting some detection criteria (such as brightness).
  False otherwise.
> I wish, using WAVE or IDL, to:
>
  1. Group together adjacent detected pixels.
     If I want to get fancy, I might try to group together detected
>
     pixels which are within a specific distance of touching.
>
>
  2. Get a something like a structure back, each element of which
     describes one such group. Each element would be an array
>
     of the coordinates of the pixels in the adjacent group.
>
> Can anyone think of an EFFICIENT way to do this that does not involve
> a massively slow loop which loops once for each detected pixel?
> (There are many, many detected points, and IDL/WAVE are rather slow
> at loops.)
> Thanks in advance for your response.
Suppose you have a one dimensional array x of dimension n
where x ne 0 for detected pixels.
Then you can find the starting offset of each group of pixels with
w = where(x(0:n-2) eq 0 and x(1:n-1) ne 0))
You'll need to handle the first pixel specially and add 1 or 2 to the
offsets
e.g.,
 IDL> a=[0,0,0,1,1,1,0,1,0,0,0,1,1,0,0,1,0,1,0]
 IDL> help,a
 Α
            INT
                    = Array(19)
 IDL> w=where(a(0:17) eq 0 and a(1:18) ne 0)
 IDL> print,w
      2
               6
                      10
                               14
                                        16
```

To handle multidimensional stuff you'll need to do something more sophisticated, but you can do similar things to get rid of at least the innermost loop.

Hope this helps, Tom McGlynn mcglynn@grossc.gsfc.nasa.gov

Subject: Re: Grouping adjacent detected pixels?
Posted by chase on Mon, 28 Aug 1995 07:00:00 GMT
View Forum Message <> Reply to Message

>>>> "Mitchell" == Mitchell R Grunes <grunes@news.nrl.navy.mil> writes:
In article <grunes.160.809624931@news.nrl.navy.mil> grunes@news.nrl.navy.mil (Mitchell R Grunes) writes:

Mitchell> Subject: Grouping adjacent detected pixels?

Mitchell> I have an image of "detected" points--

Mitchell> True for pixels meeting some detection criteria (such as brightness).

Mitchell> False otherwise.

Mitchell> I wish, using WAVE or IDL, to:

Mitchell> 1. Group together adjacent detected pixels.

Mitchell> If I want to get fancy, I might try to group together detected

Mitchell> pixels which are within a specific distance of touching.

If you only want to groups as adjacent pixels, try the LABEL_REGION command that comes with IDL. If you want a distance larger than 1 for "adjancent" pixels you can combine DILATE (or convolution with a more general kernel) with label_region and AND the result with your original image.

Chris

--

Bldg 24-E188
The Applied Physics Laboratory
The Johns Hopkins University
Laurel, MD 20723-6099
(301)953-6000 x8529
chris.chase@jhuapl.edu