Subject: Basic cgMap and cgMapPlotS tutorial Posted by Brian Daniel on Mon, 17 Sep 2012 17:26:32 GMT

View Forum Message <> Reply to Message

I've never worked much with maps in IDL, so now that I need to, I thought I'd start with the Coyote tools. From the documentation, the cgMapPlotS object seems like exactly what I need, which is to plot specific lat/lons onto a map with continents or other shapefiles on top.

Here's my code:

center_lat = 36.099510 center_lon = -5.3362050 latXRange = [35.905270, 36.171590] lonYRange = [-5.6205900, -5.0512100]

; Create cgMap object
oMap = Obj_New('cgMap', 'UTM', /LatLon_Ranges, \$
Center_Latitude=center_lat,Center_Longitude=center_lon,\$
XRange=latXRange,YRange=lonYRange, /Window,\$
Position=[0.05,0.95,0.05,0.95],Title='cgMap Test',Land_Color='brown')

print, latXRange, lonYRange

The above code prints:

4669305.1 4713144.8 -801136.78 -722963.25

So latRange and lonRange's values were changed, I'm assuming to be in units of meters. center_lat/lon values are unchanged. Then, I attempt to create a cgMapPlotS object to plot the center_lat and center_lon position with a symbol:

oMapPlotS = Obj_New('cgMapPlotS', oMap, color='red', Lats=center_lat, Lons=center_lon, PSym=1)

I get the following error:

CGMAPPLOTS::INIT--> CGCONTAINER::INIT: Incorrect number of arguments.

The only argument asked of cgMapPlotS is that of a cgMap object, which I provided. What am I missing?

Thanks in advance!

-Brian

Subject: Re: Basic cgMap and cgMapPlotS tutorial Posted by David Fanning on Mon, 17 Sep 2012 21:33:48 GMT

Brian J. Daniel writes:

> I've never worked much with maps in IDL, so now that I need to, I thought I'd start with the Coyote tools. From the documentation, the cgMapPlotS object seems like exactly what I need, which is to plot specific lat/lons onto a map with continents or other shapefiles on top.

```
> Here's my code:
>
> center_lat = 36.099510
> center lon = -5.3362050
> latXRange = [35.905270, 36.171590]
> lonYRange = [-5.6205900, -5.0512100]
> ; Create cqMap object
> oMap = Obj_New('cgMap', 'UTM', /LatLon_Ranges, $
  Center_Latitude=center_lat,Center_Longitude=center_lon,$
   XRange=latXRange, YRange=lonYRange, /Window,$
>
   Position=[0.05,0.95,0.05,0.95], Title='cgMap Test', Land_Color='brown')
>
>
> print, latXRange, lonYRange
>
 The above code prints:
      4669305.1
                    4713144.8
>
     -801136.78
                    -722963.25
>
> So latRange and lonRange's values were changed, I'm assuming to be in units of meters.
center lat/lon values are unchanged. Then, I attempt to create a cgMapPlotS object to plot the
center_lat and center_lon position with a symbol:
> oMapPlotS = Obj New('cgMapPlotS', oMap, color='red', Lats=center lat, Lons=center lon,
PSym=1)
> I get the following error:
> CGMAPPLOTS::INIT--> CGCONTAINER::INIT: Incorrect number of arguments.
> The only argument asked of cgMapPlotS is that of a cgMap object, which I provided. What am
I missing?
```

Well, this is sort of embarrassing. :-(

This cgMapPlotS program is not suppose to be in the Coyote Library. I had very nice mapping functionality in the Catalyst Library, but it seemed too complicated to me to bring it over to the Coyote Library. I wanted something much simpler there.

Anyway, long story short, this was an experiment that I quickly gave

up on. I don't think I ever really tested the darn thing, because what you found here is clearly a bug that dates back to it's Catalyst origin. It is one of several bugs in the program, I think.

Rather, I turned my attention to making the cgPlotS command work on maps in exactly the same way it worked on normal plots. The cgPlotS command would be called like this:

```
cgPlotS, center_lon, center_lat, PSYM=1, color='red', MAP=oMap
```

Unfortunately, even this wouldn't work with your code, however, as I think you have gotten a bit confused about which direction lats (Y direction) and lons (X direction) go in.

Getting all this sorted out, your code will look like this:

```
center_lat = 36.099510
center_lon = -5.3362050
latYRange = [35.905270, 36.171590]
lonXRange = [-5.6205900, -5.0512100]
oMap = Obj_New('cgMap', 'utm', /LatLon_Ranges, $
    Center_Latitude=center_lat,Center_Longitude=center_lon,$
    XRange=lonXRange, YRange=latYRange, $
    Position=[0.1,0.1,0.90,0.90],Title='cgMap Test',$
    Land_Color='brown', /Window)
cgPlotS, center_lon, center_lat, PSYM=1, color='red', MAP=oMap, /AddCmd
cgMap_Grid, /Box_Axes, Map=oMap, /AddCmd
```

Note, too, that your "center_lat" and "center_lon" values are not exactly in the center of your map ranges. Thus, your point is not drawn in the center of the map. :-)

Sorry for the confusion. I'll see what I can do to get rid of that strange program.

Cheers,

David

--

David Fanning, Ph.D.
Fanning Software Consulting, Inc.
Coyote's Guide to IDL Programming: http://www.idlcoyote.com/
Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Subject: Re: Basic cgMap and cgMapPlotS tutorial Posted by Brian Daniel on Wed, 19 Sep 2012 19:36:25 GMT

View Forum Message <> Reply to Message

On Monday, September 17, 2012 1:26:32 PM UTC-4, Brian J. Daniel wrote:

> I've never worked much with maps in IDL, so now that I need to, I thought I'd start with the Coyote tools. From the documentation, the cgMapPlotS object seems like exactly what I need, which is to plot specific lat/lons onto a map with continents or other shapefiles on top.

```
>
>
> Here's my code:
>
>
> center lat = 36.099510
>
 center_lon = -5.3362050
>
 latXRange = [35.905270, 36.171590]
>
> lonYRange = [-5.6205900, -5.0512100]
>
>
  ; Create cqMap object
>
  oMap = Obj_New('cgMap', 'UTM', /LatLon_Ranges, $
>
   Center_Latitude=center_lat,Center_Longitude=center_lon,$
>
>
   XRange=latXRange, YRange=lonYRange, /Window,$
>
>
   Position=[0.05,0.95,0.05,0.95], Title='cgMap Test', Land_Color='brown')
>
>
>
  print, latXRange, lonYRange
>
>
>
  The above code prints:
>
      4669305.1
                    4713144.8
>
>
      -801136.78
                    -722963.25
>
>
>
>
```

> So latRange and lonRange's values were changed, I'm assuming to be in units of meters. center_lat/lon values are unchanged. Then, I attempt to create a cgMapPlotS object to plot the
center_lat and center_lon position with a symbol:
>
>
>
> oMapPlotS = Obj_New('cgMapPlotS', oMap, color='red', Lats=center_lat, Lons=center_lon, PSym=1)
>
>
>
> I get the following error:
>
>
> COMADDI OTCUNIT - COCONTAINIEDUNIT, incorrect number of excuments
> CGMAPPLOTS::INIT> CGCONTAINER::INIT: Incorrect number of arguments.
>
> >
The only argument asked of cgMapPlotS is that of a cgMap object, which I provided. What am
I missing?
> >
>
>
> Thanks in advance!
>
> -Brian
Whew! I thought I was going crazy. Thanks for the update.