

---

Subject: Re: autocorrelation help

Posted by on Fri, 25 Jan 2013 23:03:54 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

On Friday, January 25, 2013 10:52:50 PM UTC+1, Kat wrote:

> Hey guys,

>

> I'm trying to run an autocorrelation on a 2D plot and it is giving me way crazy/bad results.

Seems simple enough, but it doesn't seem to be giving me what I should be expecting. I ran the following simple example below:

>

>

>

> a=indgen(100)\*.2-2

>

> b=sin(a)

>

> lag=[-7,-6,-5,-4,-3,-2,-1, 1.0,2,3,4,5,6,7]

>

>

>

>

>

> Here are the values in column form for easy viewing:

>

>

>

> ENVI> print, transpose(lag)

>

> -7.00000

>

> -6.00000

>

> -5.00000

>

> -4.00000

>

> -3.00000

>

> -2.00000

>

> -1.00000

>

> 1.00000

>

> 2.00000

>

> 3.00000

```

>
> 4.00000
>
> 5.00000
>
> 6.00000
>
> 7.00000
>
>
>
>
> ENVI> print, transpose(autocorr)
>
> 0.777030
>
> 0.808242
>
> 0.839966
>
> 0.872025
>
> 0.904238
>
> 0.936422
>
> 0.968397
>
> 0.968397
>
> 0.936422
>
> 0.904238
>
> 0.872025
>
> 0.839966
>
> 0.808242
>
> 0.777030
>
>
>
> I may be mistaken, but in this instance I have three "sin" type curves which repeat roughly
every 6 units. So for lag 6ish, the autocorrelation value should be going back up close to 1-ish.
Yet this doesn't seem to be the case in my code.
>
> Can someone help explain to me why this is not working? And hopefully suggest some way to

```

make it work?

>

> Thanks guys!

Several issues here.

First, I don't know what [a,b] is doing in that call. I assume you meant to calculate the autocorrelation of b:

```
autocorr=a_correlate(b, lag)
```

Second, sure a sine repeats after  $2\pi = 6$  but your sampling is in steps of 0.2, so the sine repeats after  $5 \times 2\pi = 31$  array elements so your lag vector is too short for you to see the second peak.

Third, that second peak will be rather attenuated because 31 is a significant part of 100 (the number of elements in your array), so you may want to try this instead:

```
a=indgen(1000)*.2-2
b=sin(a)
lag=indgen(40)
autocorr=a_correlate(b, lag)
print,autocorr
```

The result is:

1.00000	0.979339	0.919713	0.823575	0.694829	0.538665
0.361360	0.170019	-0.0277101	-0.223938	-0.410852	-0.581026
-0.727717	-0.845127	-0.928641	-0.975000	-0.982433	-0.950722
-0.881211	-0.776744	-0.641553	-0.481085	-0.301784	-0.110828
0.0841515	0.275381	0.455253	0.616624	0.753107	0.859314
0.931081	0.965615	0.961622	0.919338	0.840526	0.728402
0.587498	0.423488	0.242950	0.0531106		

And you can see the second peak at a lag of about 30 elements. Plot autocorr vs the 0.2 sampling and the peak will show up at  $2\pi$  as it should.

---

Subject: Re: autocorrelation help  
Posted by [Oana Coman](#) on Fri, 25 Jan 2013 23:38:23 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

On Friday, January 25, 2013 5:03:54 PM UTC-6, Mats Löfdahl wrote:

> On Friday, January 25, 2013 10:52:50 PM UTC+1, Kat wrote:

>  
>> Hey guys,  
>  
>>  
>  
>> I'm trying to run an autocorrelation on a 2D plot and it is giving me way crazy/bad results.

Seems simple enough, but it doesn't seem to be giving me what I should be expecting. I ran the following simple example below:

```
>
>>
>
>>
>
>>
>
>> a=indgen(100)*.2-2
>
>>
>
>> b=sin(a)
>
>>
>
>> lag=[-7,-6,-5,-4,-3,-2,-1, 1.0,2,3,4,5,6,7]
>
>>
>
>>
>
>>
>
>>
>
>>
>
>> Here are the values in column form for easy viewing:
>
>>
>
>>
>
>>
>
>> ENVI> print, transpose(lag)
>
>>
>
>> -7.00000
>
>>
>
>> -6.00000
>
>>
```

```
>
>> -5.00000
>
>>
>
>> -4.00000
>
>>
>
>> -3.00000
>
>>
>
>> -2.00000
>
>>
>
>> -1.00000
>
>>
>
>> 1.00000
>
>>
>
>> 2.00000
>
>>
>
>> 3.00000
>
>>
>
>> 4.00000
>
>>
>
>> 5.00000
>
>>
>
>> 6.00000
>
>>
>
>> 7.00000
>
>>
```

```
>
>>
>
>>
>
>> ENVI> print, transpose(autocorr)
>
>>
>
>> 0.777030
>
>>
>
>> 0.808242
>
>>
>
>> 0.839966
>
>>
>
>> 0.872025
>
>>
>
>> 0.904238
>
>>
>
>> 0.936422
>
>>
>
>> 0.968397
>
>>
>
>> 0.968397
>
>>
>
>> 0.936422
>
>>
>
>> 0.904238
>
>>
```

```

>
>> 0.872025
>
>>
>
>> 0.839966
>
>>
>
>> 0.808242
>
>>
>
>> 0.777030
>
>>
>
>>
>
>> I may be mistaken, but in this instance I have three "sin" type curves which repeat roughly
every 6 units. So for lag 6ish, the autocorrelation value should be going back up close to 1-ish.
Yet this doesn't seem to be the case in my code.
>
>>
>
>> Can someone help explain to me why this is not working? And hopefully suggest some way to
make it work?
>
>>
>
>> Thanks guys!
>
>
>
> Several issues here.
>
>
>
> First, I don't know what [a,b] is doing in that call. I assume you meant to calculate the
autocorrelation of b:
>
>
>
> autocorr=a_correlate(b, lag)
>
>

```

```

>
> Second, sure a sine repeats after  $2\pi = 6$  but your sampling is in steps of 0.2, so the sine
repeats after  $5 \cdot 2\pi = 31$  array elements so your lag vector is too short for you to see the second
peak.
>
>
>
> Third, that second peak will be rather attenuated because 31 is a significant part of 100 (the
number of elements in your array), so you may want to try this instead:
>
>
>
> a=indgen(1000)*.2-2
>
> b=sin(a)
>
> lag=indgen(40)
>
> autocorr=a_correlate(b, lag)
>
> print,autocorr
>
>
>
> The result is:
>
>      1.00000   0.979339   0.919713   0.823575   0.694829   0.538665
>
>      0.361360   0.170019  -0.0277101  -0.223938  -0.410852  -0.581026
>
>     -0.727717  -0.845127  -0.928641  -0.975000  -0.982433  -0.950722
>
>     -0.881211  -0.776744  -0.641553  -0.481085  -0.301784  -0.110828
>
>      0.0841515   0.275381   0.455253   0.616624   0.753107   0.859314
>
>      0.931081   0.965615   0.961622   0.919338   0.840526   0.728402
>
>      0.587498   0.423488   0.242950   0.0531106
>
>
>
> And you can see the second peak at a lag of about 30 elements. Plot autocorr vs the 0.2
sampling and the peak will show up at  $2\pi$  as it should.

```

Oh! I was confused about what lag actually was.  
That makes more sense. Thanks!