Subject: Why interleaving in image??

Posted by Suresh Negi on Tue, 06 Sep 2016 08:31:12 GMT

View Forum Message <> Reply to Message

Why we have to use interleaving in image in IDL.

Please tell me meaning of this.. How image size is different from image dimension.

imageSize = imageInfo.dimensions

image = READ\_IMAGE(file)

imageDims = SIZE(image, /DIMENSIONS)

interleaving = WHERE((imageDims NE imageSize[0]) AND (imageDims NE imageSize[1])) + 1

PRINT, 'Type of Interleaving = ', interleaving

Subject: Re: Why interleaving in image??

Posted by Michael Galloy on Wed, 07 Sep 2016 04:52:39 GMT

View Forum Message <> Reply to Message

On 9/6/16 2:31 AM, Sanu wrote:

> Why we have to use interleaving in image in IDL.

> Please tell me meaning of this.. How image size is different from image dimension.

>

- > imageSize = imageInfo.dimensions
- > image = READ\_IMAGE(file)
- > imageDims = SIZE(image, /DIMENSIONS)
- > interleaving = WHERE((imageDims NE imageSize[0]) AND (imageDims NE imageSize[1])) + 1
- > PRINT, 'Type of Interleaving = ', interleaving

>

When there are many channels to an image, you end up with a 3-dimensional cube of images instead of just a single m by n array. But this gives three choices for the dimensions when you have a cube: m by n by nbands (band sequential), m by nbands by n (band interleaved by pixel), or nbands by m by n (band interleaved). These simply indicate the order the bytes are stored (which can effect performance depending on how you intend to access the data).

Mike

--

Michael Galloy

www.michaelgalloy.com

Modern IDL: A Guide to IDL Programming (http://modernidl.idldev.com)

Subject: Re: Why interleaving in image??

Posted by Suresh Negi on Wed, 07 Sep 2016 10:15:04 GMT

View Forum Message <> Reply to Message

```
On Wednesday, September 7, 2016 at 10:22:43 AM UTC+5:30, Michael Galloy wrote:
> On 9/6/16 2:31 AM, Sanu wrote:
>> Why we have to use interleaving in image in IDL.
>> Please tell me meaning of this.. How image size is different from image dimension.
>>
>> imageSize = imageInfo.dimensions
>> image = READ IMAGE(file)
>> imageDims = SIZE(image, /DIMENSIONS)
>> interleaving = WHERE((imageDims NE imageSize[0]) AND (imageDims NE imageSize[1])) +
1
>> PRINT, 'Type of Interleaving = ', interleaving
>>
>
> When there are many channels to an image, you end up with a
> 3-dimensional cube of images instead of just a single m by n array. But
> this gives three choices for the dimensions when you have a cube: m by n
> by nbands (band sequential), m by nbands by n (band interleaved by
> pixel), or nbands by m by n (band interleaved). These simply indicate
> the order the bytes are stored (which can effect performance depending
> on how you intend to access the data).
>
> Mike
> Michael Galloy
> www.michaelgalloy.com
> Modern IDL: A Guide to IDL Programming (http://modernidl.idldev.com)
```

Thank you.