Subject: constant time cadence

Posted by gunvicsin11 on Thu, 20 Apr 2017 10:39:16 GMT

View Forum Message <> Reply to Message

Hi all,

I have a set of data with time cadence of 6s, 7s, 8s sometimes 11s, 80s, 300s like that. But I want them to be of constant 360s time cadence. How can I do that, anybody have idea. thanks

Subject: Re: constant time cadence

Posted by natha on Thu, 20 Apr 2017 12:46:07 GMT

View Forum Message <> Reply to Message

Interpolation (see function interpol) or nearest neighbor. Example:

```
n=10
new_data=replicate(!values.f_nan,n)
new_time=lindgen(n)*300L

for i=0L, n-1 do begin
    dist=min(abs(your_time - new_time[i]),pos)
    if dist lt 5 then new_data[i]=your_data[pos]
endfor
```

In this example "your\_time" and "your\_data" are you arrays. Note that I set a tolerance of 5 seconds, you could change that...

Using interpol, would be something like:

new\_data=interpol(your\_data,your\_time,new\_time)

Subject: Re: constant time cadence Posted by Matthew Argall on Thu, 20 Apr 2017 12:46:12 GMT

View Forum Message <> Reply to Message

Via interpolation.

```
;Create sample time and data arrays

time = [0:720:6]

time = [time, [time[-1] + 7:time[-1]+728:7] ]

time = [time, [time[-1] + 8:time[-1]+728:8] ]

time = [time, [time[-1] + 11:time[-1]+770:11] ]

time = [time, [time[-1] + 80:time[-1]+800:80] ]

time = [time, [time[-1] + 300:time[-1]+900:300] ]
```

data = FIndGen( N\_Elements(time) )

;Create desired time cadence and interpolate data tout = [time[0]:time[-1]:360.0] dout = Interpol(data, time, tout)

Subject: Re: constant time cadence

Posted by lecacheux.alain on Thu, 20 Apr 2017 12:58:24 GMT

View Forum Message <> Reply to Message

Le jeudi 20 avril 2017 12:39:19 UTC+2, sid a écrit :

- > Hi all,
- > I have a set of data with time cadence of 6s , 7s , 8s sometimes 11s, 80s, 300s like that. But I want them to be of constant 360s time cadence. How can I do that, anybody have idea.
- > thanks

new\_data = INTERPOLATE(data, INTERPOL(dindgen(times.length), times, new\_times)

Subject: Re: constant time cadence

Posted by lecacheux.alain on Thu, 20 Apr 2017 12:59:48 GMT

View Forum Message <> Reply to Message

Le jeudi 20 avril 2017 12:39:19 UTC+2, sid a écrit :

- > Hi all,
- > I have a set of data with time cadence of 6s, 7s, 8s sometimes 11s, 80s, 300s like that. But I want them to be of constant 360s time cadence. How can I do that, anybody have idea.
- > thanks

new\_data = INTERPOLATE(data, INTERPOL(dindgen(times.length), times, new\_times))

Subject: Re: constant time cadence

Posted by gunvicsin11 on Fri, 21 Apr 2017 07:21:42 GMT

View Forum Message <> Reply to Message

On Thursday, April 20, 2017 at 4:09:19 PM UTC+5:30, sid wrote:

- > Hi all,
- > I have a set of data with time cadence of 6s , 7s , 8s sometimes 11s, 80s, 300s like that. But I want them to be of constant 360s time cadence. How can I do that, anybody have idea.
- > thanks

Thanks everyone for the help, But I dont want to do interpolation. Its ok if I have approximately 360s. I need to addup the time cadence and bring to approximately 360s. How can I do this automatically.

Subject: Re: constant time cadence Posted by natha on Fri, 21 Apr 2017 12:42:31 GMT View Forum Message <> Reply to Message

Use my nearest neighbor code