Subject: DC_Read_Free in IDL?
Posted by Andre Csillaghy on Wed, 13 Mar 1996 08:00:00 GMT
View Forum Message <> Reply to Message

Hello,

I am "translating" PV-WAVE routines into IDL. In PV-WAVE, there is a routine called DC_Read_Free which is very practical to read ASCII columns files (where e.g. you can choose which column to read etc.) However the source code is not available.

Does something similar exist for IDL?

Thanks -- Andre

Subject: Re: dc_read

Posted by Seth Nemesure on Wed, 17 Dec 1997 08:00:00 GMT

View Forum Message <> Reply to Message

Matt Howard wrote:

> Use the resize switch.

>

> stat=dc_read_free(file,a,resize=[1])

The resize command works if you haven't used rebin to change the dimensions of one or more of the arrays. It appears to me that if you rebin any of the variables in the dc_read_free variable list, resize doesn't seem to have any effect on the rebinned variable or any of the variables that

appears after the rebinned variable.

--

SETH NEMESURE e-mail: seth@bnl.gov Environmental Chemistry Division http://www.ecd.bnl.gov/~seth Brookhaven National Laboratory phone: (516)344-5595 75 Rutherford Dr., Bldg. 815E fax: (516)344-2887

Upton NY 11973-5000, USA