
Subject: Re: gotcha: indexing into a scalar
Posted by [davidf](#) on Sat, 18 Jan 1997 08:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

Paul Ricchiazzi writes about IDL's ability to subscript scalar values:

> Is this feature carried over to latter versions of IDL?

Not only is it carried over to later versions of IDL, but I am sure the really expert IDL programmers like Ray Sterner and others will tell you that it has become an indispensable component of their own programming styles. :-)

Just to give you one example, some people use it to prevent scalar variables from being passed by reference in IDL programming calls. (Subscripted variables are passed by value, not by reference.) Consider this program:

```
PRO DOUBLE, number
number = number * 2
END
```

Compare the results if I do this:

```
IDL> a = 5
IDL> DOUBLE, a
IDL> Print, a
      10
```

As opposed to this:

```
IDL> a = 5
IDL> DOUBLE, a(0)
IDL> Print, a
      5
```

Interest has sort of fallen off for the IDL Expert Programmers Convention (too many people holding their breath for IDL 5.0, I hear), but this is the sort of thing that *might* have gotten you invited. ;-)

David

David Fanning, Ph.D.
Fanning Software Consulting
2642 Bradbury Court, Fort Collins, CO 80521
Phone: 970-221-0438 Fax: 970-221-4762

E-Mail: davidf@dfanning.com

Coyote's Guide to IDL Programming: <http://www.dfanning.com>