Subject: Re: 3-D scatter plot routines?
Posted by davidf on Thu, 05 Jun 1997 07:00:00 GMT
View Forum Message <> Reply to Message

## Dan Peduzzi writes:

- > I have many points of the form (x,y,z) which I would like
- > to display using IDL. Ultimately, I would like to fit a
- > surface to these data, but because they do not conform to
- > any grid, I don't think I can use the SFIT procedure (which
- > requires a 2-D array of data to fit.)

>

> Do I have any other options, using IDL 3.5?

Typically, XYZ points must be gridded to a 2D array to be displayed with the Surface command. This is usually done with the Triangulate and Trigrid procedures.

Here is an example program from my soon (thank goodness!) to be complete book that might give you an idea of how this is done.

Cheers,

David

; Create the random data. Set the seed so you see what I see.

seed = 1L x = RANDOMU(seed, 32) y = RANDOMU(seed, 32) $z = EXP(-3 * ((x - 0.5)^2 + (y - 0.5)^2))$ 

; Load a color table and create colors for the scatterplot.

LOADCT, 38, NCOLORS=!D.N\_COLORS-2 TVLCT, [70,255], [70,255], [70,0], !D.N\_COLORS-2 zcolors = BYTSCL(z, TOP=!D.N\_COLORS-3)

; Set up side-by-side viewing.

WINDOW, /Free, XSize=700, YSize=450 !P.MULTI = [0,2,1]

; Set the 3D coordinate space with axes.

SURFACE, DIST(5), /NODATA, /SAVE, XRANGE=[0,1], \$
YRANGE=[0,1], ZRANGE=[0, 1], XSTYLE=1, \$
YSTYLE=1, ZSTYLE=1, CHARSIZE=1.5, COLOR=!D.N\_COLORS-1, \$
BACKGROUND=!D.N\_COLORS-2

; Plot the random points in 3D space with a diamond shape.

PLOTS, x, y, z, PSYM=4, COLOR=zcolors, SYMSIZE=2.5, /T3D

; Connect the data points to the XY plane of the plot.

FOR j=0,31 DO PLOTS, [x(j), x(j)], [y(j), y(j)], [0, z(j)], \$ COLOR=zcolors(j), /T3D

; Now grid the data so you can display a surface on top.

Triangulate, x, y, triangles thisSurface = TriGrid(x, y, z, triangles, /Smooth) s = SIZE(thisSurface) xx = Findgen(s(1))/(s(1)-1) yy = Findgen(s(2))/(s(2)-1)

SURFACE, thisSurface, xx, yy, CHARSIZE=1.5, \$
COLOR=!D.N\_COLORS-1, ZRANGE=[0,1]

!P.MULTI = 0

**END** 

David Fanning, Ph.D.
Fanning Software Consulting
Customizable IDL Programming Courses

Phone: 970-221-0438 E-Mail: davidf@dfanning.com

Coyote's Guide to IDL Programming: http://www.dfanning.com IDL 5 Reports: http://www.dfanning.com/documents/anomaly5.html

Subject: Re: 3-D scatter plot routines?

Posted by Harald Frey on Thu, 05 Jun 1997 07:00:00 GMT

View Forum Message <> Reply to Message

## Dan Peduzzi wrote:

>

- > I have many points of the form (x,y,z) which I would like
- > to display using IDL. Ultimately, I would like to fit a
- > surface to these data, but because they do not conform to

- > any grid, I don't think I can use the SFIT procedure (which
- > requires a 2-D array of data to fit.)

Use the IDL procedure slicer.

Harald Frey Space Sciences Laboratory University of California Berkeley, CA 94720 hfrey@ssl.berkeley.edu