
Subject: idl v5.0: widget change logical name DECW\$USER_DEFAULTS ??

Posted by [Gilles Ratel](#) on Fri, 13 Jun 1997 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

Here I work with IDL v5.0 on alphaServer with OS openVMS v6.2-1H3.

I start with:

```
$ show logical DECW$USER_DEFAULTS
"DECW$USER_DEFAULTS" = "DISK$USER:[RATEL.XDEFAULTS]"
(LNM$PROCESS_TABLE)
"DECW$USER_DEFAULTS" = "SYS$LOGIN:" (DECW$LOGICAL_NAMES)
1 "SYS$LOGIN" = "AXP2$4:[RATEL]" (LNM$JOB_81635C80)
```

next with idl:

(a very very small program :-)

```
$ IDL
IDL> id = WIDGET_BASE()
IDL> exit
```

and look the logical name:

```
AXP2$ show logical DECW$USER_DEFAULTS
"DECW$USER_DEFAULTS" = ".0." (LNM$PROCESS_TABLE)
"DECW$USER_DEFAULTS" = "SYS$LOGIN:" (DECW$LOGICAL_NAMES)
1 "SYS$LOGIN" = "AXP2$4:[RATEL]" (LNM$JOB_81635C80)
```

I don't understand: logical DECW\$USER_DEFAULTS change ?????

Do you have this problem?

Thanks

Gilles

ratel@ccfm.ireq.ca
