
Subject: axis and the like

Posted by [Martin Schultz](#) on Thu, 04 Dec 1997 08:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

David Fanning wrote:

>
> Martin Schultz (mgs@io.harvard.edu) screams for help when he writes:
> [...]

the solution is

```
xyouts, 0.5, 0.88, /Normal, Align=0.5, 'H!L2!NO [ppmv]'
```

Uff! Thanks David! I was actually thinking of xyouts too, but in my vicious circle I was too stubborn to abandon the idea that this should be possible with the axis command.

The other thing I came across today again (it happens about once every two months, but I always forget the solution to it) is how to switch off the axis labeling (answer: [xyz]tick... -see, I forgot again- ...name = replicate(" ",30)). This is useful if one wants to stack a few plots that share a common x axis and display different species or the same species at different altitudes etc. Wouldn't it be nice to have a simple /NOLABEL option with the plot command ? In fact, this would have one other advantage (or do I miss something here?): If you loop through your plots, you could write something like:

```
for i=0,nplots-1 do begin
  !p.position=[llx,lly(i),llx+wx,lly(i)+wy]
  if (i eq 0) then nolabel=0 else nolabel=1
  plot,x,y(i,*),...,nolabel=nolabel
endfor
```

I don't see any way how one could do this now, except copying the plot command with all the thousand parameters and have one including the tickname statement and the other without.

Regards,
Martin.

Dr. Martin Schultz
Department for Earth&Planetary Sciences, Harvard University
186 Pierce Hall, 29 Oxford St., Cambridge, MA-02138, USA

phone: (617)-496-8318

fax : (617)-495-4551

e-mail: mgs@io.harvard.edu

IDL-homepage: <http://www-as.harvard.edu/people/staff/mgs/idl/>

Subject: Re: axis and the like

Posted by [Kevin Ivory](#) on Fri, 05 Dec 1997 08:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

David Fanning wrote:

- > Kevin Ivory and Tim Osborn both came up with the same
- > method for suppressing axis labels. Kevin wrote:

Actually, I was more proud of the second method that doesn't call another external function. ;-)

- > But what I've always done (and I am ashamed to say I
- > don't even *really* know why it works) is this:
- >
- > Plot, data, XTickformat='(A1)'

The answer is, you are printing the first character of whatever STRING makes of your numerical tick value. In most cases that will be a space. To get the idea of what happens, compare

```
print, format='(a)', 1.  
and  
print, format='(a1)', 1.
```

I tried to find an example where your method fails, but that is not as easy as I thought - perhaps impossible.

Cheers

Kevin

--

Kevin Ivory Tel: +49 5556 979 434
Max-Planck-Institut fuer Aeronomie Fax: +49 5556 979 240
Max-Planck-Str. 2 <mailto:Kevin.Ivory@linmpi.mpg.de>
D-37191 Katlenburg-Lindau, GERMANY <http://www.gwdg.de/~kivory2/>
