
Subject: Re: working with restored values

Posted by [Cathy Campo](#) on Mon, 02 Mar 1998 08:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

> Cathy Campo (campo@gav.gat.com) writes:

>
> I am restoring a save file (i do not know the names of the
> variables in advance or their data type), and displaying some of the
> variable names to the user to choose from in a droplist.
>
> restore, 'junk.sav'
> help, output=tmpstr
> varlist = strarr(5)
> varlist = tmpstr(0:4)
> widget_control, droplist, set_value=varlist
>
> i would like to save the actual values of the variables in a
> array of pointers. (have this be the uvalue of the droplist?)
> but how would i do this?
>
> later i would be using the array of pointers in the event
> loop of the droplist to do calculations with the value chosen.

David Fanning wrote:

> I would try something like this:
>
> varValues = FltArr(5)
> For j=0,4 DO ok = Execute('varValues[j] = ' + varlist[j])
> Widget_Control, droplist, Set_Value=varlist, Set_UValue=varValues

David's suggestion would be good if I knew that all of the variables were of data type 'float', but I don't. So using his advice and my idea of pointers, I am able to do this:

```
restore, 'junk.sav'
help, output=tmpstr
varlist = strarr(5)
varlist = tmpstr[0:4]
widget_control, droplist, set_value=varlist
; store varlist in uvalue of base widget
ptr = ptrarr(5, /allocate_heap)
for i = 0, 4 do ok = execute('*ptr[i] = ' + varlist[i])
widget_control, droplist, set_uvalue=ptr
```

in the event loop i am able to do this:

```
; get back varlist from uvalue of base widget
```

```
widget_control, droplist, get_uvalue=ptr
nvars = n_elements(varlist)
for i = 0, nvars-1 do begin
    print, varlist[i]
    help, *ptr[i]
endfor
```

Cathy

Subject: Re: working with restored values
Posted by [davidf](#) on Mon, 02 Mar 1998 08:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

Cathy Campo (campo@gav.gat.com) writes:

```
> I am restoring a large save file, and displaying some of the
> variable names to the user to choose from in a droplist.
>
> restore, 'junk.sav'
> help, output=tmpstr
> varlist = strarr(5)
> varlist = tmpstr(0:4)
> widget_control, droplist, set_value=varlist
>
> i would like to save the actual values of the variables in a pointer
> array or structure. (have this be the uvalue of the droplist?)
> but how would i do this?
>
> later i would be using the pointer array or structure in the event
> loop of the droplist to do calculations with the value chosen.
```

I presume from this that you do NOT know the names of the variables in advance. I would try something like this:

```
varValues = FltArr(5)
For j=0,4 DO ok = Execute('varValues[j] = ' + varlist[j])
Widget_Control, droplist, Set_Value=varlist, Set_UValue=varValues
```

Cheers,

David

David Fanning, Ph.D.
Fanning Software Consulting
E-Mail: davidf@dfanning.com

Phone: 970-221-0438

Coyote's Guide to IDL Programming: <http://www.dfanning.com/>
