
Subject: Re: Double-Precision Byte Swap
Posted by [Peter Mason](#) on Tue, 28 Apr 1998 07:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

On 28 Apr 1998, R. Kyle Justice wrote:
> Using PV-Wave in UNIX, is there a way to read
> double-precision floating point data generated
> on a PC?
> I think I need something something similar to
> the BYTEORDER procedure, but I need to (or do I?)
> swap 8 instead of 4 bytes.

Assuming that the data are IEEE double-precision (almost certainly), yes, you just need to reverse the order of each number's 8 bytes.
(But note that if it's Digital Unix that you're using then you should NOT re-order.)

I don't use PV-Wave, but here's a little IDL routine for the job:

```
=====
; Reverse the byte order of a whatever
pro bytere, v
j=size(v) &nj=n_elements(j) &t=j(nj-2) &n=j(nj-1)
if (t le 1) or (t ge 7) then return ;undefined, or inappropriate type
case t of
  2:byteorder,v,/sswap ;short
  3:byteorder,v,/lswap ;long
  4:byteorder,v,/lswap ;float
  5:begin &for i=0L,n-1L do v(i)=double(rotate(byte(v(i),0,8),2),0) &end ;double
  6:byteorder,v,/lswap ;complex (it works, too!)
endcase
return
end
=====
```

Peter Mason

Subject: Re: Double-Precision Byte Swap
Posted by [rkj](#) on Wed, 29 Apr 1998 07:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

R. Kyle Justice (rkj@dukebar.crml.uab.edu) wrote:
: : Assuming that the data are IEEE double-precision (almost certainly), yes, you
: : just need to reverse the order of each number's 8 bytes.
: : (But note that if it's Digital Unix that you're using then you should NOT
: : re-order.)

```

: : I don't use PV-Wave, but here's a little IDL routine for the job:
: : ;=====
: : ; Reverse the byte order of a whatever
: : pro bytere, v
: : j=size(v) &nj=n_elements(j) &t=j(nj-2) &n=j(nj-1)
: : if (t le 1) or (t ge 7) then return ;undefined, or inappropriate type
: : case t of
: :   2:byteorder,v,/sswap ;short
: :   3:byteorder,v,/lswap ;long
: :   4:byteorder,v,/lswap ;float
: :   5:begin &for i=0L,n-1L do v(i)=double(rotate(byte(v(i),0,8),2),0) &end ;double
: :   6:byteorder,v,/lswap ;complex (it works, too!)
: : endcase
: : return
: : end
: : ;=====

```

: : Peter Mason

: Works like a charm! This ought to be in the user library.

: Thanks.

: Kyle

Actually, a similar routine (wbyteorder.pro) is indeed in the pv-wave user library. I guess I didn't look hard enough . . . but I still like the elegance of this solution.

Kyle

Subject: Re: Double-Precision Byte Swap
 Posted by [rkj](#) on Wed, 29 Apr 1998 07:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

: Assuming that the data are IEEE double-precision (almost certainly), yes, you
 : just need to reverse the order of each number's 8 bytes.
 : (But note that if it's Digital Unix that you're using then you should NOT
 : re-order.)

```

: : I don't use PV-Wave, but here's a little IDL routine for the job:
: : ;=====
: : ; Reverse the byte order of a whatever
: : pro bytere, v
: : j=size(v) &nj=n_elements(j) &t=j(nj-2) &n=j(nj-1)

```

```

: if (t le 1) or (t ge 7) then return ;undefined, or inappropriate type
: case t of
:   2:byteorder,v,/sswap ;short
:   3:byteorder,v,/lswap ;long
:   4:byteorder,v,/lswap ;float
:   5:begin &for i=0L,n-1L do v(i)=double(rotate(byte(v(i),0,8),2),0) &end ;double
:   6:byteorder,v,/lswap ;complex (it works, too!)
: endcase
: return
: end
: ;=====

```

: Peter Mason

Works like a charm! This ought to be in the user library.

Thanks.

Kyle
