
Subject: OPENW using /XDR (IDL 5.1/linux) WARNING!
Posted by [Russ Welti \(on mapper\)](#) on Fri, 10 Jul 1998 07:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

The 5.1 online help for OPENW states that /XDR option is basically obsolete but does NO harm to be present (for backward compatibility).

But I finally found my problem in porting a huge IDL application from my Solaris 5.0 IDL workstation to my test linux box, and it was definitely due to the presence of the /XDR on an OPENW statement.

I presume this is a bug, if it is not, i would very much appreciate being contacted to tell me otherwise, so i can maintain my IDL source code properly (i.e. single copy of the source code, not both a 5.0 and a 5.1+ version)

Below, i have included a tiny example session where the error is displayed.

```
IDL> print,path
/home/saga/geno/rwelti/ceph/C30-3AH/
IDL> openw,unit,path+"/tst.bin",/get_lun,/XDR
IDL> writeu,unit,float(1.0)
IDL> free_lun,unit
IDL> r=float(0.0)
IDL> openr,unit,path+"/tst.bin",/get_lun
IDL> readu,unit,a
IDL> help,a
A          FLOAT    =  4.60060e-41
% Program caused arithmetic error: Floating underflow

IDL> free_lun,unit
IDL> openw,unit,path+"/tst.bin",/get_lun    <== NO /XDR here
IDL> writeu,unit,float(1.0)
IDL> free_lun,unit
IDL> r=float(0.0)
IDL> openr,unit,path+"/tst.bin",/get_lun
IDL> readu,unit,a
IDL> help,a
A          FLOAT    =    1.00000
```

Sincerely,

Russ Welti /
 /-\

(c-g)

University of Washington \-/

Molecular Biotechnology /

PO Box 357730 /-

Seattle, WA 98195 (a-t)

rwelti@u.washington.edu \-/

(206) 616 5116 voice (206) 685 7301 FAX /
