Subject: Re: EXECUTE limits? Posted by Thomas A. McGlynn on Mon, 21 Dec 1998 08:00:00 GMT View Forum Message <> Reply to Message

Alex Schuster wrote:

```
> Wayne Landsman wrote:
>> In practice, I find the V5.0 EXECUTE limits the same as they were in V4.0.
>>
>> In the example below, I try to use EXECUTE to define an anonymous
>> structure at run-time. (Note that I can't use the CREATE STRUCT
>> function, because CREATE_STRUCT requires that one know the number of tags
                  This works fine so long as the EXECUTE string does not
>> beforehand.)
>> exceed a certain length -- which seems to vary from machine to machine.
>> Otherwise I get a "Program code area full" error message.
> I experienced that such long statements work in compiled code only, not
> at the command line or via EXECUTE. BTW, this worked even better in IDL
 4.
>
>
  But you can use CREATE STRUCT this way:
>
> IDL> d = { name:0 }
> IDL> for i = 0, 99 do d = create_struct( d, 'name' + strtrim(i,2), 0 )
>
       Alex
>
```

The problem with the approach you give is that you need to have a variable of the type you wish the structure element to be. E.g., if I know that ...the 54th element is to be a fltarr(10,10,10) and the 55th is a double... where the types are defined dynamically then I need to do something like:

```
for i=0, number of fields
  strng = "fld = "+typestring(i)
  execute(strng)
  d = create struct(d, name(i), fld)
endfor
```

where I've collected the names and the type definitions into character arrays. So I have to do an execute as well as a create_struct for every line.

I've also been shown that IDL has a problem with structure definitions of the form:

```
str = {a1: 0,a2:0, ... a996:0}
```

for very large structures -- although such structures can be built piecemeal as you describe above.

The solution I've adopted (and sent to Wayne) is try to optimize the number of calls to execute and create struct so that we have:

```
names = ['name1', 'name2', ...]
types = ['0', 'fltarr(10)', 'double(10,10)', '1.0'...]

str = mrd_struct(names, types)

and in MRD_STRUCT we do something like:

for(each field) do begin
   while (length of strng fits in EXECUTE buffer) do begin
    strng = strng + names(i)+":"+types(i)
   endwhile
   execute("substr = {"+strng+"}")
   total_str = create_struct(total_str, substr)
   endfor
   execute("substr = {"+strng+"}")
   total_str = create_struct(total_str, substr)
```

This retains a lot more flexibility than the IDL standard create_struct but minimizes the number of calls to execute and create_struct.

My testing seems to indicate that it's reasonably efficient up to a thousand or so fields, but it does slow up substantially then -- though that may be that IDL has trouble with the very large structures.

Regards, Tom McGlynn tam@silk.gsfc.nasa.gov

Subject: Re: EXECUTE limits?
Posted by Alex Schuster on Mon, 21 Dec 1998 08:00:00 GMT
View Forum Message <> Reply to Message

Wayne Landsman wrote:

- > In practice, I find the V5.0 EXECUTE limits the same as they were in V4.0.
- > In the example below, I try to use EXECUTE to define an anonymous

- (Note that I can't use the CREATE_STRUCT > structure at run-time.
- > function, because CREATE_STRUCT requires that one know the number of tags
- This works fine so long as the EXECUTE string does not > beforehand.)
- > exceed a certain length -- which seems to vary from machine to machine.
- > Otherwise I get a "Program code area full" error message.

I experienced that such long statements work in compiled code only, not at the command line or via EXECUTE. BTW, this worked even better in IDL 4.

But you can use CREATE_STRUCT this way:

```
IDL> d = \{ name: 0 \}
IDL> for i = 0, 99 do d = create_struct( d, 'name' + strtrim(i,2), 0 )
```

Alex

Alex Schuster Wonko@weird.cologne.de alex@pet.mpin-koeln.mpg.de

PGP Key available