
Subject: Thoughts on IDL5.2 GuiBuilder and library widgets
Posted by [Michael W Asten](#) on Fri, 15 Jan 1999 08:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

Thought I might share a few comments on idl library guis, and on the idl 5.2 GuiBuilder.

I have passed these comments on to RSI, and had some useful feedback. As far as my requests go, they have been added to the RSI customer request list; maybe if other users see similar needs and write in to rsi, then the requests will be correspondingly higher on the priority list. I should add the caveat that i speak as a scientific user of idl, not as a programmer, so my perspective will probably be naive to the expert users.

The GuiBuilder: (a bouquet) It is an excellent interface, very easy to use after getting the hang of it. It does need more documentation at even simpler level than that in the online doc provided .

In particular, the base widget has a pull-down menu capability, which can be used to build a program "launcher" with great ease.

The IDL5.2 guibuilder is also great for building labels, and buttons, and the necessary program links.

(a brickbat): the present version of the GuiBuilder cant build complex widgets; this means building a set of fields to get mixed integers, real numbers and strings into and out of a widget is difficult. In fact I cant for the life of me make use or sense of the GuiBuilder "text widget"; the amount of programming needed to catch the various delete/insert/singleChar/multipleChar options seems pointless when the ancient (and much maligned) WIDED (from idl 4.x) can build a compound-widget gui for fields quickly (altho clumsily).

A useful trick to get a set of fields into a gui for editing/selection, is to use the XVAREEDIT routine. If (say) we want to enter a title (string) and four axis limits (reals) for a plot, then an instant gui for entering/editing those parameters

can be obtained by passing all the parameters to XVAREDIT as a structure; XVAREDIT allows each element of a structure to be edited in a field separately, and the structure tags provide prompts to the user (example code appended below).

I prefer the obsolete version of XVAREDIT from idl4.x, but the idl5.x version also works (but be warned) needs double clicks to open cells for editing, and the Enter key to 'accept' an edited value.

This opens another issue I have found; IDL has a few very powerful library widgets, dialog_pickfile, dialog_message, xdisplayfile, xvaredit) but the on-line documentation says virtually nothing about them in general chapters, so a new user can be completely ignorant of the friendly features that can get a program up and running quickly, without widget programming needed. It would be useful to add an online chapter on "Hints for getting the best out of library guis". The most obviously "missing" library widget is a generalised version of xvaredit which might allow calls in the form

xvaredit, var, list=list,prompt=prompt
where var is an array (strings, int or reals),
list is an array of same length of strings used as labels alongside each element of var,
and prompt is a title/directive explaining what the selections are for.

A couple of other widgets which I suggest should be in a core library are a

1) color bar for direct graphics images (its an FAQ I know, and the Coyote has one on his website, but why isnt such an obvious item included by arrangement with the idl distribution?)
2) a 'fuel-gauge' widget to show progress within a slowly executing loop (call un update to the fuel gauge at each loop commencement). Everyone will have their own favorite "indispensables".

Regards,
Michael Asten
masten@earth.monash.edu.au
;=====

```

; program to demonstrate use of XVAREDIT for editing mixed string and
;     real numbers, in a widget
; this works in idl 5.x, but note the edit process on each cell of the
widget
;     requires a double click to "activate" the cell, and a Press Enter

;     to confirm changes to the cell.
; This program works more cleanly and more intuitively with the
different
;     procedure (of the same name) XVAREDIT in IDL 4.x
;     (in directory \rsi\idl40\lib).
;
; demo by Michael Asten, Monash University, Melbourne. 9 Jan 99.
;
x=10.*indgen(5*36)
y=sin(x!*pi/180)
plot,x,y
xmin=0 & xmax=(5*360) & ymin=-1. & ymax=1.
title='XVAR TEST'
print,title,xmin,xmax,ymin,ymax
; now set up a structure to pass plot parameters to an edit widget
plot_par={plot_title:title,Xaxis_left_limit:xmin,Xaxis_right_limit:xmax,
$,
           Yaxis_lower_limit:ymin,Yaxis_top_limit:ymax}
xvaredit,plot_par           ; edit the parameters in a widget
title=plot_par.plot_title   ; now extract the edited parameters
from the structure
xmin=plot_par.Xaxis_left_limit
xmax=plot_par.Xaxis_right_limit
ymin=plot_par.Yaxis_lower_limit
ymax=plot_par.Yaxis_top_limit

print,title,xmin,xmax,ymin,ymax ; print the new values
plot,x,y,title=title,xrange=[xmin,xmax],yrange=[ymin,ymax] ; draw the
new plot
end
; =====

```
