Subject: Re: Retrieve content of Droplist

Posted by mgs on Mon, 03 May 1999 07:00:00 GMT

View Forum Message <> Reply to Message

In article <MPG.1197dd3be091b1c598978e@news.frii.com>, davidf@dfanning.com (David Fanning) wrote:

> Thomas C. Stubbings (stubbing@fbch.tuwien.ac.at ) writes:

> ...

>> WID\_DROPLIST\_RULEWT = Widget\_Droplist(WID\_BASE\_0, \$

> Widget\_Control, info.droplistID, Get\_UValue=dropValues

> P.S. This is only about the 10th time I've answered this

> question. I think I'll make a tip and put it on my web page.

Be sure to add it to the FAQ, too :-)

Folks, just to make sure everyone knows what's available, if you have something that you see often, please feel free to add it to the FAQ at <a href="http://www.ivsoftware.com:591/FAQ/">http://www.ivsoftware.com:591/FAQ/</a>

Afterwards, drop a line to the newsgroup about any additions or changes. I'd really like to see this take off and be a great resource for all of us.

--

Mike Schienle mgs@ivsoftware.com http://www.ivsoftware.com/ Interactive Visuals, Inc.
Remote Sensing and Image Processing
Analysis and Application Development

Subject: Re: Retrieve content of Droplist Posted by davidf on Mon, 03 May 1999 07:00:00 GMT View Forum Message <> Reply to Message

Thomas C. Stubbings (stubbing@fbch.tuwien.ac.at ) writes:

- > Although it may be trivial, I cannot manage to retrieve the currently
- > selected value of a droplist (the online help of IDL is somehow a bad
- > joke...). It is defined as follows:

>

- > WID\_DROPLIST\_RULEWT = Widget\_Droplist(WID\_BASE\_0, \$
- > UNAME='WID\_DROPLIST\_RULEWT' ,XOFFSET=4 ,YOFFSET=45 \$
- > ,SCR\_XSIZE=135 ,SCR\_YSIZE=23 ,TITLE='Fusion rule' ,VALUE=[\$
- > 'average', 'waverage', 'maximum', 'minimum', 'himaximum', \$
- > 'hifirst', 'hisecond', 'hi/lo', 'lo/hi' ])

When you are in the business I'm in, this is what is known as "good marketing", not a "bad joke". :-)

You can obtain the index number of the current droplist selection like this. (I assume the droplist identifier is in the "info" structure, and that the droplist "values" are in the UVALUE of the droplist, so they are handy.)

Widget\_Control, info.droplistID, Get\_UValue=dropValues currentSelection = Widget\_Info(info.droplistID, /Droplist\_Select) Print, dropValues[currrentSelection]

Cheers,

David

P.S. This is only about the 10th time I've answered this question. I think I'll make a tip and put it on my web page.

--

David Fanning, Ph.D.

Fanning Software Consulting

Phone: 970-221-0438 E-Mail: davidf@dfanning.com

Coyote's Guide to IDL Programming: http://www.dfanning.com/

Toll-Free IDL Book Orders: 1-888-461-0155

Subject: Re: Retrieve content of Droplist Posted by Henry Chapman on Mon, 03 May 1999 07:00:00 GMT View Forum Message <> Reply to Message

```
"Thomas C. Stubbings" wrote:
> Although it may be trivial, I cannot manage to retrieve the currently
> selected value of a droplist (the online help of IDL is somehow a bad
> joke...). It is defined as follows:
>
   WID_DROPLIST_RULEWT = Widget_Droplist(WID_BASE_0, $
     UNAME='WID DROPLIST RULEWT', XOFFSET=4, YOFFSET=45 $
>
      ,SCR XSIZE=135,SCR YSIZE=23,TITLE='Fusion rule',VALUE=[$
>
      'average', 'waverage', 'maximum', 'minimum', 'himaximum', $
>
     'hifirst', 'hisecond', 'hi/lo', 'lo/hi' 1)
>
> Can anyone help? Thanks!
> Thomas
```

In your event procedure:

wid\_droplist = widget\_info(event.top, find\_by\_uname='WID\_DROPLIST\_RULEWT') selected = widget\_info(wid\_droplist, /droplist\_select)

From the widget\_info help:

DROPLIST SELECT

This keyword applies to widgets created with the WIDGET\_DROPLIST function.

Set this keyword to return the zero-based number of the currently-selected element (i.e., the currently-displayed element) in the specified droplist widget.

Henry.

--

Henry Chapman mailto:chapman9@llnl.gov Information Science & Technology Program phone:(925)423-1580 Lawrence Livermore National Lab fax:(925)423-1488 L-395, 7000 East Ave., Livermore CA 94550