Subject: Re: behavior of arrays Posted by Pavel Romashkin on Wed, 19 May 1999 07:00:00 GMT View Forum Message <> Reply to Message

I do not quite realize what is the point in this exercise. FLTARR(10,1) is an array with 10 columns and 1 row (which all is meaningful only in the direction of array operations which in IDL is row-wise). Therefore, seems to me that FLTARR(10, 1) is the same as FLTARR(10) to begin with (unlike FLTARR(1, 10)). If you anticipate expanding the matrix, its easy to do by using TRANSPOSE and subscripts. I have never experienced a problem with losing or mixing up dimensions, although most of my data are matrices. In the example below, I see no loss of information in the transition from d to c. If you defined more than 1 row, C would be 2D in the last statement.

Cheers.

```
Pavel
"R.Bauer" wrote:
> I have some problems to understand the logic which may be behind the
> handling of an array
> like defined.
 Why is the result help, b.d only [10] and not [10,1]?
 This means I will lose the information that's it is / was a 2-dim
  dataset.
> R.Bauer
> d=reform(findgen(10),10,1)
> help,d
> ;D
             FLOAT
                       = Array[10, 1]
> b=create_struct('d',d)
> help,b,/str
>
 ;** Structure <1348428>, 1 tags, length=40, refs=1:
 ; D
               FLOAT Array[10, 1]
>
>
> help,b.d
  ; <Expression> FLOAT = Array[10]
> c=b.d
> help.c
> ; C
              FLOAT
                        = Array[10]
```

Subject: Re: behavior of arrays
Posted by Craig Markwardt on Wed, 19 May 1999 07:00:00 GMT
View Forum Message <> Reply to Message

Don't get me started on this again. You can find my recent tirade on this subject under "dropped dimensions" on dejanews.com.

For the case of your structure, I think that b.d is *actually* still a 10x1 array, but any access to it will cause IDL to automatically collapse the degenerate dimension in the expression. Therefore, even HELP thinks that it is a 10-vector, not a 10x1 array.

Practically speaking, you will need to REFORM() your array whenever you need to use it.

Craig

"R.Bauer" <R.Bauer@fz-juelich.de> writes:

```
> I have some problems to understand the logic which may be behind the
> handling of an array
> like defined.
>
> Why is the result help, b.d only [10] and not [10,1]?
> This means I will lose the information that's it is / was a 2-dim
> dataset.
> d=reform(findgen(10),10,1)
> help,d
> :D
             FLOAT = Array[10, 1]
>
> b=create_struct('d',d)
> help,b,/str
> ;** Structure <1348428>, 1 tags, length=40, refs=1:
> ; D FLOAT Array[10, 1]
>
>
> help,b.d
> ; <Expression> FLOAT = Array[10]
Craig B. Markwardt, Ph.D. EMAIL: craigmnet@astrog.physics.wisc.edu
Astrophysics, IDL, Finance, Derivatives | Remove "net" for better response
```
