

---

Subject: Re: INTERPOL question

Posted by [landsman](#) on Wed, 09 Jun 1999 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

In article <Pine.BSF.4.05.9906091216370.28548-100000@mtolympus.ari.net>,

Anil Kochhar <[anilk@mtolympus.ari.net](mailto:anilk@mtolympus.ari.net)> wrote:

> Hi All,  
>  
> I am using IDL Version 5.2 (SUNOS Sparc) and am having some trouble  
> using the INTERPOL function in idl. I have several pairs of arrays of  
> data. One of the Array pairs is an array of time and the other array  
> holds a measurement (i.e. data point) at the corresponding time.  
>  
> I used the following command to interpolate the arrays:  
>  
> Pair2DataNew = Interpol (Pair2Time, Pair2Data, Pair1Time)  
> Pair3DataNew = Interpol (Pair3Time, Pair3Data, Pair1Time)  
> Pair4DataNew = Interpol (Pair4Time, Pair4Data, Pair1Time)  
> Pair5DataNew = Interpol (Pair5Time, Pair5Data, Pair1Time)  
>

It looks like you have the X and Y parameters reversed, and for example,  
the first line should read

Pair2DataNew = Interpol( Pair2Data, Pair2Time, Pair1Time)

Other potential problems with using Interpol (although probably not in  
your case) include

1. Not using a monotonic input X parameters (e.g. Pair2Time)
2. INTERPOL extrapolates beyond the edges, so you can get bizarre  
results if you try to extrapolate too far on non-smooth data.

--Wayne Landsman

[landsman@mpb.gsfc.nasa.gov](mailto:landsman@mpb.gsfc.nasa.gov)

Sent via Deja.com <http://www.deja.com/>  
Share what you know. Learn what you don't.

---