Subject: xwindow question

Posted by Nando lavarone on Thu, 01 Jul 1999 07:00:00 GMT

View Forum Message <> Reply to Message

<HTML>

Hi all,

I'm using the david fanning's "xwindow" procedure.

I used it with the keyword "wid" to make other oeparations

on the display window.

I need to have the PS output of currently display and not

of the starting display.

<P>Has anyone just modified the procedure to do that?

<P>Thank you.

<PRE>--

Nando lavarone

Advanced Computer System - SPACE DIVISION

via Lazzaro Belli, 23

00040 Frascati - RM

Tel: +39-6-944091 (switchboard)

E-mail:

f.iavarone@acsys.it

FrdndVrn@altavista.net</PRE>

</HTML>

Subject: Re: xwindow question

Posted by Nando lavarone on Tue, 06 Jul 1999 07:00:00 GMT

View Forum Message <> Reply to Message

<HTML>

David Fanning wrote:

<BLOCKQUOTE TYPE=CITE>Martin Schultz (mgs@io.harvard.edu) writes:

<P>> Seems like the author isn't aware of his genius? ;-)

<P>You obviously haven't had a recent conversation with my

wife, thank goodness. :-(</BLOCKQUOTE>

Often the genius cannot be universal; o) ,but speaking about IDL I agree with Martin.

<P>Not only I have integrated the xwindow in my system,

but I have learned a lot about keywords use and the EXTRA

keyword (thank you).

<P>I added in the xwindow code a check to set automatically

the PREVIEW keyword when encapsulated postscript button is set.

<P>Thank you.

<PRE>-- :

Nando lavarone

Advanced Computer System - SPACE DIVISION

via Lazzaro Belli, 23

00040 Frascati - RM

Tel: +39-6-944091 (switchboard)

E-mail:

f.iavarone@acsys.it

FrdndVrn@altavista.net</PRE>

</HTML>

Subject: Re: xwindow question

Posted by rmlongfield on Thu, 08 Jul 1999 07:00:00 GMT

View Forum Message <> Reply to Message

In article <377B85B3.CA76EF40@acsys.it>,

Nando lavarone <f.iavarone@acsys.it> wrote:

>

- > -----6F80BD925244E9F1DEA21E5F
- > Content-Type: text/plain; charset=us-ascii
- > Content-Transfer-Encoding: 7bit

>

- > Hi all,
- > I'm using the david fanning's "xwindow" procedure.
- > I used it with the keyword "wid" to make other opparations
- > on the display window.
- > I need to have the PS output of currently display and not
- > of the starting display.

Hi Nando,

By coincidence I have just tried working with XWINDOW.

It works for the default if I type xwindow. But if I try:

XWINDOW, 'SURFACE', Dist(20), Charsize=1.5

I get these error messages:

XWINDOW: Incorrect number of arguments.

Maybe I don't understand completely how this function works but I have

the feeling I am just missing something.

Did you encounter these errors? Can you give me a hint about what I might be doing wrong?

I use { mipseb IRIX unix 5.2 Oct 30 1998}

Thanks, Rose

Sent via Deja.com http://www.deja.com/ Share what you know. Learn what you don't.