

Posted by [Nando Iavarone](#) on Thu, 01 Jul 1999 07:00:00 GMT

the PREVIEW keyword when encapsulated postscript button is set.

<P>Thank you.

```
<PRE>--&nbsp;;
```

Nando lavarone

Advanced Computer System - SPACE DIVISION

via Lazzaro Belli, 23

00040&nbsp; Frascati - RM

Tel: +39-6-944091 (switchboard)

9440968 (direct)

E-mail:

 f.iavarone@acsys.it

```
    FrdndVrn@altavista.net
```

 </HTML>

Subject: Re: xwindow question

Posted by [rmlongfield](#) on Thu, 08 Jul 1999 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

In article <377B85B3.CA76EF40@acsys.it>,

Nando Iavarone <f.iavarone@acsys.it> wrote:

 $\triangleright$

```
> -----6F80BD925244E9F1DEA21E5F
```

```
> Content-Type: text/plain; charset=us-ascii
```

- > Content-Transfer-Encoding: 7bit

 $\succ$

> Hi all,

```
> I'm using the david fanning's "xwindow" procedure.
```

> I used it with the keyword "wid" to make other operations

> on the display window.

> I need to have the PS output of currently display and not

> of the starting display.

Hi Nando,

By coincidence I have just tried working with XWINDOW.

It works for the default if I type xwindow. But if I try:

```
XWINDOW, 'SURFACE', Dist(20), Charsize=1.5
```

I get these error messages:

XWINDOW: Incorrect number of arguments.

Maybe I don't understand completely how this function works but I have the feeling I am just missing something.

Did you encounter these errors? Can you give me a hint about what I might be doing wrong?

I use { mipseb IRIX unix 5.2 Oct 30 1998}

Thanks,
Rose

Sent via Deja.com <http://www.deja.com/>
Share what you know. Learn what you don't.
